



HERKULES

Multipurpose hose for challenging applications as for example fire brigades, refineries, airports, ports and industry use.

- CONSTRUCTION**
- 100% synthetic yarn, circular woven, high-end nitrile/PVC-blend – extruded through the weaving in one production process.

- ADVANTAGES**
- maximum adhesion between nitrile/PVC-blend and weaving
 - resistant to low and high temperatures (-20°C up to + 100°C)
 - resistant to seawater
 - abrasion resistant, durable
 - resistant to oil, petrol and other chemicals
 - UV-light and ozone resistant

| i.D. in inch | Dia. in mm | wall thickness mm | weight gr/m | WP / TP / BP in bar | Artikel-Nr. |
|--------------|------------|-------------------|-------------|---------------------|-------------|
| 1 1/2 | 38 | 2,00 | 360 | 20/40/60 | 600621 |
| 1 3/4 | 45 | 2,00 | 400 | 20/40/60 | 600631 |
| 2 | 52 | 2,20 | 470 | 20/40/60 | 600622 |
| 2 1/2 | 63 | 2,40 | 620 | 16/32/50 | 600623 |
| 2 3/4 | 70 | 2,40 | 680 | 16/32/50 | 600629 |
| 3 | 75 | 2,40 | 750 | 16/32/50 | 600624 |
| 4 | 102 | 2,70 | 1060 | 16/32/50 | 600625 |

V1.0