



V1.0



**KSS**

internal  
weaving



Synthetic fibre hose with weaving inside to bunch, respectively to protect cables and cords.

**WEAVING**

- high tenacity multifilament polyester yarn, circular woven
- 2-ply warp threads, hardwearing and abrasion resistant

**LINING**

- ageing- and ozone resistant EPDM rubber-lining
- smooth, excellent adhesion
- manufactured in a special vulcanizing process

| dia. in mm    | wall thickness | weight g/m | article-nr. |
|---------------|----------------|------------|-------------|
| 20,0 – 21,0   | 1,5mm          | 80         | KSS020      |
| 25,0 – 26,0   | 1,5mm          | 105        | KSS025      |
| 28,0 – 29,0   | 1,5mm          | 115        | KSS028      |
| 32,0 – 33,0   | 1,5mm          | 130        | KSS032      |
| 35,0 – 36,0   | 1,5mm          | 150        | KSS035      |
| 40,0 – 41,0   | 1,5mm          | 185        | KSS040      |
| 45,0 – 46,0   | 1,5mm          | 200        | KSS045      |
| 52,0 – 53,0   | 1,5mm          | 210        | KSS052      |
| 60,0 – 61,0   | 1,5mm          | 235        | KSS060      |
| 70,0 – 71,0   | 1,5mm          | 340        | KSS070      |
| 75,0 – 76,0   | 1,5mm          | 370        | KSS075      |
| 90,0 – 91,0   | 1,5mm          | 500        | KSS090      |
| 110,0 – 111,0 | 1,5mm          | 575        | KSS110      |
| 125,0 – 126,0 | 1,5mm          | 660        | KSS125      |

Antistatic version (> 10.000V) on request!