



KURALON

Quality and attractive prices made this hose popular, especially for industry use and ship chandlers. Certified to HED/Solas and EN 14.540 (applicable for cabinets according to EN 671-2).

WEAVING

- high tenacity multifilament polyester yarn, circular woven
- 2-ply warp threads, hardwearing and abrasion resistant

LINING

- ageing- and ozone resistant EPDM rubber-lining
- resistant to low and high temperatures

OUTER COATING

additional protection against mechanical and chemical damage on request

gr/m in bar 1 25 100 15/25/45 KU 1 1/2 38 180 15/25/45 KU 1 3/4 42/45 210 15/25/45 KU 2 52 240 15/25/45 KU 2 1/2 63 290 15/25/45 KU 2 1/2 65 290 15/25/45 KU 2 3/4 70 340 15/25/45 KU					
1 1/2 38 180 15/25/45 KU 1 3/4 42/45 210 15/25/45 KU 2 52 240 15/25/45 KU 2 1/2 63 290 15/25/45 KU 2 1/2 65 290 15/25/45 KU 2 3/4 70 340 15/25/45 KU	i.d. in inch	dia. in mm	-		article-nr.
1 3/4 42/45 210 15/25/45 KU 2 52 240 15/25/45 KU 2 1/2 63 290 15/25/45 KU 2 1/2 65 290 15/25/45 KU 2 3/4 70 340 15/25/45 KU	1	25	100	15/25/45	KUW025
2 52 240 15/25/45 KU 2 1/2 63 290 15/25/45 KU 2 1/2 65 290 15/25/45 KU 2 3/4 70 340 15/25/45 KU	1 1/2	38	180	15/25/45	KUW038
2 1/2 63 290 15/25/45 KU 2 1/2 65 290 15/25/45 KU 2 3/4 70 340 15/25/45 KU	1 3/4	42/45	210	15/25/45	KUW045
2 1/2 65 290 15/25/45 KU 2 3/4 70 340 15/25/45 KU	2	52	240	15/25/45	KUW052
2 3/4 70 340 15/25/45 KU	2 1/2	63	290	15/25/45	KUW063
	2 1/2	65	290	15/25/45	KUW065
	2 3/4	70	340	15/25/45	KUW070
3 75 400 15/25/45 KU	3	75	400	15/25/45	KUW075

